


FORM PTO-1390 (REV 11-98)	U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER 36-1359
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371		U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.5) 097623977 (To Be Assigned)
INTERNATIONAL APPLICATION NO. PCT/GB99/01061	INTERNATIONAL FILING DATE 7 April 1999	PRIORITY DATE CLAIMED 8 April 1998
TITLE OF INVENTION TELECONFERENCING SYSTEM		
APPLICANT(S) FOR DO/EO/US HUGHES		
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:		
1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). 4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19 th month from the earliest claimed priority date. 5. A copy of the International Application as filed (35 U.S.C. 371(c)(2)).		
a. <input checked="" type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). <input type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).		
a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input type="checkbox"/> have not been made and will not be made. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (U.S.C. 371(c)(3)). <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).		
Items 11. To 16. Below concern document(s) or information included:		
11. <input type="checkbox"/> An Information Disclosure Statement under 37 C.F.R. 1.97 and 1.98. 12. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 C.F.R. 3.28 and 3.31 is included. 13. <input checked="" type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 14. <input type="checkbox"/> A substitute specification. 15. <input type="checkbox"/> A change of power of attorney and/or address letter. 16. <input type="checkbox"/> Other items or information.		

U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.5) (To Be Assigned) 09/1623977		INTERNATIONAL APPLICATION NO. PCT/GB99/01061		ATTORNEY'S DOCKET NUMBER 36-1359																																																																																																								
17. <input checked="" type="checkbox"/> The following fees are submitted: BASIC NATIONAL FEE (37 C.F.R. 1.492(a)(1)-(5)): -- Neither international preliminary examination fee (37 C.F.R. 1.482) nor international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO\$970.00 -- International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO\$840.00 -- International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO\$690.00 -- International preliminary examination fee paid to USPTO (37 C.F.R. 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4)\$670.00 -- International preliminary examination fee paid to USPTO (37 C.F.R. 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4)\$96.00 <div style="text-align: right;">ENTER APPROPRIATE BASIC FEE AMOUNT =</div> <div style="display: flex; justify-content: flex-end; align-items: center;"> <div style="margin-right: 20px;">Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 C.F.R. 1.492(e)).</div> <div style="border: 1px solid black; padding: 2px;">\$ 840.00</div> </div> <table border="1" style="width:100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th style="width:20%;">CLAIMS</th> <th style="width:15%;">NUMBER FILED</th> <th style="width:15%;">NUMBER EXTRA</th> <th style="width:10%;">RATE</th> <th style="width:10%;"></th> <th style="width:10%;"></th> <th style="width:10%;"></th> </tr> </thead> <tbody> <tr> <td>Total Claims</td> <td>15</td> <td>-20 =</td> <td>0</td> <td>X</td> <td>\$18.00</td> <td>\$ 0.00</td> </tr> <tr> <td>Independent Claims</td> <td>2</td> <td>-3 =</td> <td>0</td> <td>X</td> <td>\$78.00</td> <td>0.00</td> </tr> <tr> <td colspan="5">MULTIPLE DEPENDENT CLAIMS(S) (if applicable)</td> <td>\$260.00</td> <td>\$ 0.00</td> </tr> <tr> <td colspan="5" style="text-align: right;">TOTAL OF ABOVE CALCULATIONS =</td> <td></td> <td>\$ 840.00</td> </tr> <tr> <td colspan="5">Reduction by 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed (Note 37 C.F.R. 1.9, 1.27, 1.28).</td> <td></td> <td>0.00</td> </tr> <tr> <td colspan="5" style="text-align: right;">SUBTOTAL =</td> <td></td> <td>\$ 840.00</td> </tr> <tr> <td colspan="5">Processing fee of \$130.00, for furnishing the English Translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 C.F.R. 1.492(f)).</td> <td style="text-align: center;">+</td> <td>0.00</td> </tr> <tr> <td colspan="5" style="text-align: right;">TOTAL NATIONAL FEE =</td> <td></td> <td>\$ 840.00</td> </tr> <tr> <td colspan="5">Fee for recording the enclosed assignment (37 C.F.R. 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 C.F.R. 3.28, 3.31). \$40.00 per property</td> <td style="text-align: center;">+</td> <td>\$ 40.00</td> </tr> <tr> <td colspan="5">Fee for Petition to Revive Unintentionally Abandoned Application (\$1210.00 - Small Entity = \$605.00)</td> <td></td> <td>\$ 0.00</td> </tr> <tr> <td colspan="5" style="text-align: right;">TOTAL FEES ENCLOSED =</td> <td></td> <td>\$ 880.00</td> </tr> <tr> <td colspan="5"></td> <td style="text-align: right;">Amount to be:</td> <td></td> </tr> <tr> <td colspan="5"></td> <td style="text-align: right;">refunded</td> <td>\$</td> </tr> <tr> <td colspan="5"></td> <td style="text-align: right;">Charged</td> <td>\$</td> </tr> </tbody></table>				CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE				Total Claims	15	-20 =	0	X	\$18.00	\$ 0.00	Independent Claims	2	-3 =	0	X	\$78.00	0.00	MULTIPLE DEPENDENT CLAIMS(S) (if applicable)					\$260.00	\$ 0.00	TOTAL OF ABOVE CALCULATIONS =						\$ 840.00	Reduction by 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed (Note 37 C.F.R. 1.9, 1.27, 1.28).						0.00	SUBTOTAL =						\$ 840.00	Processing fee of \$130.00, for furnishing the English Translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 C.F.R. 1.492(f)).					+	0.00	TOTAL NATIONAL FEE =						\$ 840.00	Fee for recording the enclosed assignment (37 C.F.R. 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 C.F.R. 3.28, 3.31). \$40.00 per property					+	\$ 40.00	Fee for Petition to Revive Unintentionally Abandoned Application (\$1210.00 - Small Entity = \$605.00)						\$ 0.00	TOTAL FEES ENCLOSED =						\$ 880.00						Amount to be:							refunded	\$						Charged	\$
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE																																																																																																									
Total Claims	15	-20 =	0	X	\$18.00	\$ 0.00																																																																																																						
Independent Claims	2	-3 =	0	X	\$78.00	0.00																																																																																																						
MULTIPLE DEPENDENT CLAIMS(S) (if applicable)					\$260.00	\$ 0.00																																																																																																						
TOTAL OF ABOVE CALCULATIONS =						\$ 840.00																																																																																																						
Reduction by 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed (Note 37 C.F.R. 1.9, 1.27, 1.28).						0.00																																																																																																						
SUBTOTAL =						\$ 840.00																																																																																																						
Processing fee of \$130.00, for furnishing the English Translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 C.F.R. 1.492(f)).					+	0.00																																																																																																						
TOTAL NATIONAL FEE =						\$ 840.00																																																																																																						
Fee for recording the enclosed assignment (37 C.F.R. 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 C.F.R. 3.28, 3.31). \$40.00 per property					+	\$ 40.00																																																																																																						
Fee for Petition to Revive Unintentionally Abandoned Application (\$1210.00 - Small Entity = \$605.00)						\$ 0.00																																																																																																						
TOTAL FEES ENCLOSED =						\$ 880.00																																																																																																						
					Amount to be:																																																																																																							
					refunded	\$																																																																																																						
					Charged	\$																																																																																																						
a. <input checked="" type="checkbox"/> A check in the amount of \$880.00 to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. 14-1140 in the amount of \$_____ to cover the above fees. A duplicate copy of this form is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 14-1140. A duplicate copy of this form is enclosed. d. <input type="checkbox"/> The entire content of the foreign application(s), referred to in this application is/are hereby incorporated by reference in this application. NOTE: Where an appropriate time limit under 37 C.F.R. 1.494 or 1.495 has not been met, a petition to revive (37 C.F.R. 1.137(a) or (b)) must be filed and granted to restore the application to pending status. <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> SEND ALL CORRESPONDENCE TO: NIXON & VANDERHYE P.C. 1100 North Glebe Road, 8th Floor Arlington, Virginia 22201 Telephone: (703) 816-4000 </div> <div style="width: 45%; text-align: center;">  SIGNATURE <div style="border-top: 1px solid black; display: inline-block; width: 100%;">Larry S. Nixon</div> NAME </div> </div> <div style="display: flex; justify-content: space-between; margin-top: 20px;"> <div style="width: 45%;"> 25,640 REGISTRATION NUMBER </div> <div style="width: 45%; text-align: right;"> September 11, 2000 Date </div> </div>																																																																																																												

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of

HUGHES

Atty. Ref.: 36-1359

Serial No. (To Be Assigned)

Group:

National Phase of PCT/GB99/01061

Filed: September 11, 2000

Examiner:

For: TELECONFERENCING SYSTEM

September 11, 2000

Assistant Commissioner for Patents

Washington, DC 20231

Sir:

PRELIMINARY AMENDMENT

Prior to calculation of the filing fee and in order to place the above identified application in better condition for examination, please amend the claims as follows:

IN THE CLAIMS

Claim 3, line 1, delete "or 2",

Claim 4, line 1, change "any preceding claim" to --claim 1--,

Claim 7, line 1, change "any preceding claim" to --claim 1--,

Claim 8, line 1, change "any preceding claim" to --claim 1--,

Claim 12, line 1, delete "or 11",

Claim 13, line 1, delete "11, 12",

Claim 14, line 1, change "any of claims 10 to 13" to --claim 10--.

REMARKS

The above amendments are made to place the claims in a more traditional format.

Respectfully submitted,

NIXON & VANDERHYE P.C.

By:



Larry S. Nixon

Reg. No. 25,640

LSN:ms

1100 North Glebe Road, 8th Floor

Arlington, VA 22201-4714

Telephone: (703) 816-4000

Facsimile: (703) 816-4100

433 Rec'd PCT/PTO 11 SEP 2000

1

30 Preferably the conference bridge comprises a concentrator, having means to identify the currently active input channels and to transmit only those active channels over the multichannel connection, together with control information identifying the transmitted channels. This reduces the capacity required by the multichannel connection. The control information identifying the active channels may be carried in a separate control channel, or as an overhead on the active subset of channels. In a preferred arrangement the channel representing a given terminal is excluded from the output provided to that terminal. This may be achieved by excluding that channel from the processing in the terminal equipment,

[illegible]

0 **1** **2** **3** **4** **5** **6** **7** **8** **9**

0 **1** **2** **3** **4** **5** **6** **7** **8** **9**

0 **1** **2** **3** **4** **5** **6** **7** **8** **9**

[illegible][illegible][illegible][illegible]

0 **1** **2** **3** **4** **5** **6** **7** **8** **9**

[illegible][illegible]

0 **1** **2** **3** **4** **5** **6** **7** **8** **9**

[illegible]

110, and the resulting signal transmitted over the telephone network (2) to each terminal equipment 10, (20, 30) for conversion to sound in respective loudspeakers 12, 22, 32 etc. In this way the exchange equipment 100 acts as a "bridge" to allow one or more terminal equipments 30 to connect into a simple two-way connection between terminal equipments 10, 20.

The systems illustrated in Figures 2 to 8 replace the conventional conference bridge system of Figure 1 with a multicast system in which several channels can be transmitted to each participant, using a multi-channel link comprising an uplink 3, and also a downlink which comprises a control channel 4 and a digital audio downlink 5. The audio downlink comprises several channels 51, 52. Participants with suitable terminal equipment can then process these channels 51, 52 in various ways as will be described.

The transmission medium used for the uplink 3 and downlink 4,5 can be any suitable medium. ISDN (Integrated Services Data Network) technology or LAN (Local Area Network) - respectively public and private data networks - are the favoured transmission options since they provide adequate data rate and low latency - delays due to coding and transmission buffering. However, they are expensive and to date they have a low penetration in the market place. Internet Protocol (IP) techniques are becoming widely used, but currently suffer from poor latency and unreliable data rates. However, over the next few years rapid improvements are envisaged in this technology and it is likely to become the preferred telecommunication method. Such systems would be ideally suited to implementing this invention. The latest internet type modems provide 56kbit/s downstream (links 4,5:), and up to 28.8kbit/s upstream (link 3). They are low cost and are commonly included in personal computer retail packages. Ideally a system should be able to work with all of the above, and also with standard analogue PSTN for use as a backup.

The signal mixing can take place either in the user's terminal equipment, or in a centralised processing platform as is shown in Figure 2. In Figure 2 the terminal equipment 10 contains a microphone 11 and loudspeaker system 12 as before. However, the loudspeaker system 12 is a spatialised system - that is, it has two or more channels to allow sounds to appear to emanate from different directions. This may take the form of stereophonic headphones, or a more complex system such as disclosed in United States Patents 5533129 (Gefvert), 5307415

(Fosgate), article "Spatial Sound for Telepresence" by M.Hollier, D. Burraston, and A. Rimell in the British Telecom Technology Journal, October 1997 or the present applicant's own International Patent Application WO98/58523, published on 23 December 1998.

5 The output from the microphone 11 is encoded by an encoder 13 forming part of the terminal equipment 10, and transmitted over the uplink 3 to the exchange equipment 100. Here it is combined with the other input channels 21, 31 from the other participants, terminals into a concentrator 230 which combines the various inputs into an audio signal having a smaller number of channels 51, 52
10 etc. These channels are transmitted over multiple-channel digital audio links 5 to the customer equipments 10, (20, 30) where they are first decoded by respective decoders 14, 24, 34 (Figure 3) and provided to a spatialiser 15 (Figure 4) for controlling the mixing of the channels to generate a spatialised signal in the speaker equipment 12.

15 The concentrator 230 selects from the input channels 11, 21, 31 those carrying useful information - typically those carrying speech - and passes only these channels over the return link 5. This reduces the amount of information to be carried. A control channel 4 carries data identifying which channels were selected. In the terminal equipment the spatialiser 15 uses data from the control channel to
20 identify which of the original sound channels 11, 21, 31 it is receiving, and on which of the "N" channels 51, 52 in the audio link each original channel is present, and constructs a spatialised signal using that information. The spatialised signal can be tailored to the individual customer, for example the number of talkers in the spatialised system, the customer's preferences as to where in the spatialised
25 system each participant is to seem to be located, and which channels to include.

 In particular, the user may exclude the channel representing his own input 11, or may select a simultaneous translation instead of the original talker.

 Transmission efficiency is achieved because only the active subset N of the total number of channels M are transmitted at any one time. The subset is
30 chosen using a voice controlled dynamic channel allocation algorithm in the N:M concentrator 230. A possible implementation of this is shown in Figure 8. Each input channel 11,21,31 is monitored by a respective analyser 231, 232, 233. As shown for analyser 231, the signal is subjected to a speech detection and analysis process 231b. This detects whether speech is present on the respective input 11,

and gives a confidence value, indicative of how likely it is that the signal contains speech. This ensures that low-level background speech is given a lower weight than speech clearly addressed to the microphones 11, 21, 31 etc. A value is also given for level, to ensure speech directed to the microphone is preferred over background noise, and the level information can be passed to the spatialisation system to select a coding algorithm appropriate to the information in the speech. In order to detect and process the speech in the signals they first need to be decoded in a decoder 231a (this may be dispensed with if the speech detection system 231b can operate with digitally encoded signals).

10 A voting algorithm 234 then selects which of the inputs 11, 21, 31 have the clearest speech signals and controls a switch to direct each of the input channels 11, 21, 31 which have been selected to a respective one of the output channels 51, 52. Similar algorithms are used in Digital Circuit Multiplication Equipment (DCME) systems in international telephony circuits. Data relating the audio channels' content to the conference participants, and therefore the correspondence between the input channels 11, 21, 31 and output channels 51, 52 is transmitted over the control channel 4. Alternatively, this data can be embedded in the encoded audio data.

When there are fewer talkers identified than there are available output channels 51, 52, signal quality can be improved by using a less compressed digitisation scheme for those input channels selected, thereby using more than one output channel 51, 52 for each input channel selected. Telephone quality speech may be achieved at 8kbits/s, allowing eight talkers to be accommodated if the system has a 64kbit/sec capability. Should fewer talkers be detected, the 64kbit/s capability may be used instead to provide four 16 kbit/s audio channels, capable of carrying 'good' quality speech, or a mixture of channels at different bit rates, to allow the coding rates to be selected according to the initial signal quality, or so that the main talker may be passed at higher quality than the other talkers. Layered coding schemes can be used to allow graceful switching between data rates.

The N-channel de-multiplexer and speech decoder 14 used in the terminal equipment 10 is shown in Figure 3. This receives the channels 51, 52, 53 etc carried in the audio downlink 5 and separates them in a demultiplexer 140. Each channel 51, 52, etc is then separately decoded in a respective decoder 141, 142,

143, etc for processing by the spatialiser 15. The decoders 141, 142, etc may operate according to different processes according to the individual coding algorithms used, under the control of the control signals carried in the control channel 4.

5 A composite signal consisting of the summation of all input signals could also be transmitted. Such a signal could be used by users having monaural receiving equipment, and may also be used by the spatialiser to generate an ambient background signal. Alternatively the spatialiser 15 may replace any of the channels 11, 21, 31 not selected by the concentrator 230, and therefore not
10 represented in the N channel link 5, by "comfort noise"; that is low-level white noise, to avoid the aural impression of a void which would be occasioned by a complete absence of signal.

The customer equipment 10 can be implemented using a desktop PC. Readily available PC sound card technology can provide the audio interface and processing needed for the simpler spatialising schemes. The more advanced sound cards with built in DSP technology could be used for more advanced schemes. The spatialiser 15 can use any one of a number of established techniques for creating an artificial audio environment as detailed in the Hollier et al article already referred to.

20 Spatialisation techniques may be summarised as follows. Any of these
spatialisation techniques may be used with the present invention.

The simplest technique is “panning”, where each signal is replayed with appropriate weighting via two or more loudspeakers such that it is perceived as emanating from the required direction. This is easy to implement, robust and may also be used with headphones.

“Ambisonic” systems are more complicated and employ a technique known as wavefront reconstruction to provide a realistic spatial audio percept. They can create very good spatial sound, but only for a very small listening area and are thus only appropriate for single listeners.

30 For headphone listening, “binaural” techniques can be used to provide very good spatialisation. These use head-related transfer function (HRTF) filter pairs to recreate the soundfield that would have been present at the entrance to the ear canal for a sound emanating from any position in 3D space. This can give very good spatialisation and may be extended for use with loudspeakers, when it is

known as "transaural". As with ambisonic systems, the correct listening region is very small.

The output of several spatialisers may be combined as shown in Figure 4, which shows a spatialiser group for a stereophonic output having left and right
5 channels 12L, 12R. Each channel 51, 52, 53 is fed to a respective spatialiser 151, 152, 153 which, under the control of a coefficient selector 150 control by the signals in the control channel 4, transmits an output 151L, 151R etc to each of a series of combiners 15L, 15R. The processing used to create the outputs 151L, 151R etc is operated under the control of the control signal 4 such that each
10 channel appears as a virtual sound source, having its own location in the space around the listener.

The positions of virtual sources in three dimensional space could be determined automatically, or by manual control, with the user selecting the preferred positioning for each virtual sound source. For a video conference the
15 positioning can be set to correspond with the appropriate video picture window. The video images may be sent by other means, or may be static images retrieved from local storage by the individual user.

If the spatialised sound is relayed via loudspeakers 12, rather than headphones, it will be necessary to prevent signals from the loudspeakers 12 being
20 picked up by the microphone 11, re-transmitted and being heard as an echo at the distant sites 20, 30 etc. A technique for achieving this will be described later, with reference to Figure 11.

Figure 5 shows an alternative arrangement to that of Figure 4, in which the spatialisation is computed in the conference 'bridge'. Each conference
25 participant receives the same spatialised signals, thus simplifying the customer equipment. Figure 5 is similar in general arrangement to Figure 2, except that the decoder 14 and spatialiser 15 are part of the exchange equipment 200. The output from the spatialiser 15 is passed to an encoder 18 which transmits the required number of audio channels (e.g. two for a stereo system) to each customer 10, 20,
30 30. This requires the number of channels in the downlink 5 to be equal to the number of audio channels in the spatialisation systems' outputs, instead of the number selected by the concentrator (plus the control channel 4) as in the embodiment of Figure 2. It also simplifies the customer equipment 10. However, this arrangement requires all customer installations 10, 20, 30 to have similar

spatialisation systems, and in particular the same number of audio channels. It would also be more difficult to remove a talker's own voice from the signal he receives. Echo control would also be more complicated, and channel coding may degrade the spatialisation.

5 Conventional analogue connections could be included in the conference by providing each analogue connection 43, 45 to the 'bridge' 200 with an encoder 42, as shown in Figure 6, to provide an input 41 to the concentrator. The output 5 of the concentrator 230 is also decoded and combined in a unit 44 to provide a monaural conference signal 45 to the analogue user 40.

The invention could be applied to a conference situation in which there are several participants at each location, such as the video conference shown in Figure 7. Close microphones 11a, 11b, 11c, for example of the "tie-clip" type, are used to pick up the sound from each individual talker, and a talker location system 60 is used to keep track of their spatial position. The talker location system 60 may comprise a system of microphones which can identify the positions of sound sources. Relating the position of a sound source to that of the tie clip microphone 11 currently in use makes it possible to learn the position of each talker by audio means alone. Alternatively, the system may detect the position of each user by means such as optical recognition of a badge carried by each user. In either case, the position data detected by the talker location system 60 is passed to the far end (Room B), where correct spatialisation is reconstructed, for output by loudspeakers 12L, 12M, 12R etc. This would achieve a true spatial conference and overcome associated echo control problems, since the "tie clip" microphones 31a, 31b, 31c have a limited range and will not detect the outputs from the loudspeakers in the same room.

If loudspeakers are used in the embodiments of Figures 2 to 4 or of Figure 5, there is a need to control acoustic feedback ("echo") between the loudspeaker 12 and the microphone 11. Such feedback causes signals to be retransmitted back into the system, so that each user hears one or more delayed versions of each signal (including his own transmissions) arriving from the other users. For a
30 monophonic system echo control can be done using an echo canceller as shown in Figure 9. The echo signal, represented by D, is caused by the acoustic path J between the loudspeaker 12 and microphone 11 of equipment 10 in room B. Cancellation is achieved in an echo control unit 16 by using an adaptive filter to

create a synthetic model of the signal path J such that the echo D may be removed by subtraction of a cancellation signal D'. The signal returned to equipment 20 in room A is now free of echoes, containing only sounds that originated in Room B. The optimum modelling of the acoustic path J is usually
5 achieved by the adaptive filter in a manner such that some appropriate function of the signal E is driven towards zero. Echo control using adaptive filters in this manner is well known.

Multi-channel echo cancellation, as shown in Figure 10 for two channels, is more complex since there are two input channels 51, 52 and therefore two
10 loudspeakers 12L, 12R. It is therefore necessary to model two echo paths K and L for each of the two return channels 3L, 3R. (The process is only shown for return channel 3L, using microphone 11L). Correct echo cancellation is only achieved if adaptive filters 161L, 162L model the signal paths K and L respectively. (Two further filters 161R, 162R are required for the other return channel 3R) However, it
15 is not possible to find a correct model for each path K, L independently without some difficult and expensive signal processing as described in "A better understanding and an improved solution to the specific problems of stereophonic echo cancellation" (IEEE Transactions on speech and Audio processing, Vol 6, no 2 March 1998. Authors: J Benesty, D R Morgan and M M Sondhi).

20 The system described above with reference to Figure 4 employs linear artificial spatialisation techniques. Figure 11 shows how this, and the fact that the echo from each loudspeaker 12L, 12R combines linearly at each microphone 11L, (11R, not shown), allows echo cancellation to be provided for each output channel 3L, (3R) by having a separate adaptive filter 161L, 162L, 163L, (161R, 162R,
25 163R) on each input channel 51, 52, 53. Thus the adaptive filter 161L will model the combination of the spatialiser 151 for the channel 51, and the echo path between the loudspeakers 12L and 12R and the microphone 11L. This arrangement is discussed in detail in the applicant's co-pending application claiming the same priority as the present case.

CLAIMS

1. A teleconferencing system comprising a conference bridge (100) having a
5 multichannel connection (5) to each of a plurality of terminal equipments, and at least one terminal equipment (10) having means (15) to separately process each channel to provide a plurality of outputs, each output representing one of the other terminal equipments.
- 10 2. A system according to claim 1, wherein the terminal equipment (10) has spatialisation means (15), to combine the outputs representing each terminal to provide a spatialised output in which each terminal is represented by a virtual sound source.
- 15 3. A system according to claim 1 or 2, wherein the conference bridge (100) comprises a concentrator (230), having means to identify the currently active input channels (3, 21, 31), and to transmit only those active channels over the multichannel connection (5), together with control information (4) identifying the transmitted channels.
- 20 4. A system according to any preceding claim, wherein the channel representing a given terminal is excluded from the output provided to that terminal.
5. A system according to claim 4, comprising means (16) in the terminal
25 equipment for excluding the said channel from the processing.
6. A system according to claim 4, comprising means for excluding the said channel from the multichannel transmission from the bridge (100) to the respective terminal (10).
- 30 7. A system according to any preceding claim, provided with selection means whereby the use of an individual terminal can select which channel, or channels, of the plurality of channels are to be output by the user terminal.

8. A system according to any preceding claim, the terminal equipment (10) having echo cancellation means (16) comprising means for detecting correlations between the output signal from the terminal equipment and input signals carried on individual input channels to the terminal equipment, the input signals being
5 representative of other terminals, such correlations being indicative of acoustic feedback at the terminal equipment, and means for cancelling such feedback signals in the output signal.

9. A system according to claim 8, wherein the terminal equipment (10)
10 comprises, for each channel of the output signal, a plurality of adaptive filters, each adaptive filter being arranged to model the echo path between a respective input channel and the respective output channel, and for each output channel there being provided a combiner for adding the outputs of the respective plurality of
15 adaptive filters to generate an echo cancellation signal for the respective output channel.

10. A method of providing teleconferencing services to a plurality of terminal equipments, in which a multichannel connection is provided from a conference bridge (100) to each terminal equipment (10), in which at least one terminal
20 equipment processes each channel separately to provide a plurality of outputs, such output each representing a respective one of the other terminals.

11. A method according to claim 10, wherein the outputs are processed to generate a spatialised output in which each cooperating terminal is represented by
25 a virtual sound source.

12. A method according to claim 10 or 11, wherein the conference bridge (100) identifies the currently active input channels and transmits only those active channels over the multichannel connection, together with control information
30 identifying the transmitted channels.

13. A method according to claim 10, 11, 12 wherein the channel representing a given terminal is excluded from the output provided to that terminal.

001150 16650

15

ABSTRACT

TELECONFERENCING SYSTEM

A teleconferencing system comprises a conference bridge 100 having a multichannel connection 5 to each customer equipment 10. The customer equipment 10 has means 14 to separately process each channel 51, 52, 53 to provide one output representing each of the other participants. These outputs can be combined in a spatialiser 15 to provide a spatialised output 12 in which each participant is represented by a virtual sound source. The conference bridge 100 comprises a concentrator 230, having means to identify the currently active input channels and to transmit only those active channels over the multichannel connection, together with control information identifying the transmitted channels.

Figure (2)

15




Figure 1





Figure 2

**Figure 3**




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11

RULE 63 (37 C.F.R. 1.63)
DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: TELECONFERENCING SYSTEM
the specification of which (check applicable box(es)):

☐ is attached hereto.

☐ was filed on _____ as U.S. Application Serial No. _____

☒ was filed as PCT international application No. PCT/ GB99/01061 on 07 April 1999
and (if applicable to U.S. or PCT application) was amended on _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 C.F.R. 1.56. I hereby claim foreign priority benefits under 35 U.S.C. 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed or, if no priority is claimed, before the filing date of this application:

Prior Foreign Application(s):

Application Number	Country	Day/Month/Year Filed
98302763.2	EUROPE	08 April 1998
9807745.6	GREAT BRITAIN	08 April 1998

I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below.


Application Number	Day/Month/Year Filed

I hereby claim the benefit under 35 U.S.C. 120/365 of all prior United States and PCT international applications listed above or below and, insofar as the subject matter of each of the claims of this application is not disclosed in such prior applications in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose material information as defined in 37 C.F.R. 1.56 which occurred between the filing date of the prior applications and the national or PCT international filing date of this application:

Prior U.S./PCT Application(s):

Application Serial No.	Day/Month/Year Filed	Status: patented, pending, abandoned
PCT/GB99/01061	07 April 1999	Pending

I hereby declare that all statements made herein of my own knowledge are true and that statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon. And I hereby appoint NIXON & VANDERHYE P.C., 1100 North Glebe Road, 8th Floor, Arlington, VA 22201-4714, telephone number (703) 816-4000 (to whom all communications are to be directed), and the following attorneys thereof (of the same address) individually and collectively my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent: Arthur R Crawford, 25327; Larry S. Nixon, 25640; Robert A. Vanderhye, 27076; James T. Hosmer, 30184; Robert W. Faris, 31352; Richard G. Besha, 22770; Mark E. Nusbaum, 32348; Michael J. Keenan, 32106; Bryan H. Davidson, 30251; Stanley C. Spooner, 27393; Leonard C. Mitchard, 29009; Duane M. Byers, 33363; Paul J. Henon, 33626; Jeffry H. Nelson, 30481; John R. Lastova, 33149; H. Warren Burnam Jr., 29366; Thomas E. Byrne, 32205; Mary J. Wilson, 32955; J. Scott Davidson, 33489; Alan M. Kagen, 36178; William J. Griffith, 31260; Robert A. Molan, 29834.

1. Inventor's Signature:  Date: 13 April 1999
Inventor: PETER JAMES HUGHES BRITISH
(first) MI (last) (citizenship)
Residence: (city) WOODBIDGE GB3 (state/country) GREAT BRITAIN
Post Office Address: 8 SOUTH CLOSE, MELTON, WOODBRIDGE, SUFFOLK, GREAT BRITAIN
(Zip code) IP12 1QR